

1224RSOD • 24" Outdoor Refrigerator • Outdoor Series





PERFORMANCE

- Overall volume of 5.2 cu ft holds up to 123 bottles (12 oz) or 185 cans (12 oz)
- Digital Touch Pad Control is conveniently located on upper face of unit
- Temperature range: 34°F 45°F
- Digital passive cooling system

INTERIOR/EXTERIOR

White interior is illuminated with LED lightingThree removable tempered glass shelves

- Standard professional stainless steel handle is interchangeable with commercial handle accessory
- Full stainless steel cabinet and door are deemed suitable for outdoor use by UL
- Door swing is field reversible
- Door lock is standard



STAINLESS SOLID (LOCK)

INTEGRATION

- Unit is designed to be built-in or can be freestanding with the freestanding accessory kit
- Four independently adjustable leveling legs provide a precise undercounter fit

MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-1224RSOD-00A	115 / 60	Field Reversible	Stainless Solid (Lock)	109 lbs

ACCESSORIES


Model	Description	Finish	Shipping Weight
23074	Professional Door Handle, 1 1/4" Diameter	Stainless	2 lbs
23073	Commercial Door Handle, 7/8" Diameter	Stainless	2 lbs
U-FSK-S	Freestanding Kit	Stainless	3 lbs




Outdoor Series • 24" Outdoor Refrigerator • 1224RSOD

DIMENSIONS

Dimensions shown apply to all finishes, including Integrated (INT) models with 3/4" integrated panel/frame installed.



CABINET CUT-OUT



SPECIFICATIONS

Model	1224RSOD	
Amps: Running	1.2	
Capacity: Bottle (12 oz)	123	
Capacity: Can (12 oz)	185	
Capacity: Volume (cu ft)	5.2	
Control Type	Digital Touch Pad	
Dimensions: Depth	23 ¹ / ₄ " / 591 mm	
Dimensions: Height	34 ½" / 867 mm	
Dimensions: Width	24" / 610 mm	
Energy Consumption: Avg. Per Year	240 kWh	
ENERGY STAR	ENERGY STAR	
Product Weight: Max	99 lbs	
Refrigerant Type	R600a	
Sabbath (Star K Certified)	Yes	
Temperature Range	34°F - 45°F	

INSTALLATION NOTES

When installing adjacent to wall, ensure 2-1/2" clearance on hinged side for 90° door opening, allowing ample room for door handle.

Cutout includes the additional $1/4^{\prime\prime}$ width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

COOLING SYSTEM



ELECTRICAL REQUIREMENTS

This unit requires a grounded a polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).







Please visit u-line.com to view this model's User Guide. All specifications are subject to change without notice.

Residential & Commercial

Deemed suitable for outdoor use by UL