

## Setup & Operation

1. Assemble QuickCarb™ without ball lock connectors on hoses
2. Immerse open ends of all hoses into a bucket of sanitizer and turn on pump to recirculate.
3. To drive sanitizer through the carbonation stone and hose, kink the saturation hose until sanitizer is forced through the CO2 stone and hose
4. Remove hoses from bucket and allow pump to expel sanitizer from hoses
5. Kink the saturation hose to drive the sanitizer out of the CO2 hose and stone and turn off pump
6. Connect CO2 hose to CO2 tank and purge hoses for 5 seconds
7. Connect the black ball lock to the short liquid out hose
8. De-pressurize keg and attach the black ball lock
9. Turn on pump until liquid makes it all the way through the saturation hose
10. Turn off pump, attach the gray ball lock, and connect to the keg
11. Set regulator 1-2 PSI above the desired carbonation pressure
12. Turn on pump and recirculate beer for 30-40 minutes

## Cleanup & Storage

1. Turn off pump, CO2, and disconnect ball locks from keg
2. Disconnect CO2 hose from CO2 tank and remove ball locks from hoses
3. Immerse open ends of all hoses into a bucket of warm PBW and turn on pump to recirculate
4. Kink saturation hose to drive cleaner through the stone and CO2 hose
5. Repeat step 3 & 4 with sanitizer to rinse
6. Turn off pump, remove hoses, carbonation stone, and tee fitting and hang hoses to dry

