

KALIX

bottleless Cooler



Contemporary Styling & High-Capacity Combined

The KALIX is a highly-efficient tri-temp Hot, Cook & Cold or dual-temp Cook 'N Cold™ bottleless/point-of-use water cooler.

KALIX Features

- Stylish silver & black design
- Easy, soft touch solenoid activated water dispensing
- Sealed cooling system provides a sanitary environment and reduces cleaning frequency
- Efficient cooling system with quick cold water recovery for consistent cold water dispensing
- Removable, dishwasher-safe drip tray
- Easy access to filter compartment
- Advanced energy-efficient hot tank
- High-capacity cold water delivery (one gallon per hour of water cooler than 50° F)
- Cook N' Cold, Hot, Cook & Cold models with and without filtration
- Energy Star Rated
- 5-year limited warranty
- Models:

STANDARD

Cook 'N Cold — P1PVK

Hot, Cook 'N Cold — P1PVHSK

with FILTRATION

Cook 'N Cold — PF1PVK

Hot, Cook & Cold — PF1PVHK

Available in
Hot, Cook & Cold
or Cook 'N Cold

The industry's only
cooler with the
revolutionary Pressure
Vessel Direct Chill
(PVDC) system for high
efficiency cooling



OASIS[®]

Certified
WBENC
Women's Business Enterprise

oasiscoolers.com | oasis-parts.com | 800.646.2747

KALIX specifications



A high-efficiency tri-temp Hot, Cook & Cold or dual-temp Cook 'N Cold™ bottleless/point-of-use water cooler

Cabinet: ABS plastic top and front with removable metal side panels.

Cold Water Refrigeration Unit: Convection cooled condenser. Internally spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled accurately by a capillary tube.

Cold Water Thermostat: Temperature is controlled by an adjustable thermostat with “OFF” position that is easily accessible on the rear of the cabinet.

Cold Water Reservoir: Two-piece, type 300 series stainless steel for easy cleaning and sanitizing.

Two-Piece Hot Water Tank: Energy-efficient tank is constructed of type 300 series stainless steel. The 500 watt element can be replaced on site, reducing time and service costs. Two piece hot tank is easily replaced or serviced.

Filter Models: Models with Filters include a Two-Stage Sediment & Carbon Lead Filtration System. **Green filters** are eco-friendly with reusable, refillable housings—only the filter elements need replaced.

Hot Water Capacity: 45 x 6oz. cups of piping hot water per hour. 1½ quart storage tank.

Hot Water Thermostat: Adjustable thermostat with safety limiter.

Drip Receptor: Two-piece drip tray lifts out for easy removal. Molded for durability and dishwasher safe. Can be tapped to run to a waste drain.

Electrical: 115 volts, 60 Hertz. 1/20 hp water cooler compressor. Three wire service cord and polarized plug furnished.

Dimensions: W 12 3/4” x D 13 1/2” x H 43 3/4”

Approximate Net Weight:

Cook 'N Cold | P1PVK | PF1PVK 51lbs.

Hot 'N Cold | P1PVHSK | PF1PVHSK 55lbs.

Energy consumption:

Cook N' Cold™, Model P1PVK.121 kwh/day

Hot, Cook N' Cold, Model P1PVHSK .546 kwh/day

Lead-Free: Components in this water cooler are lead-free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model Listed by Underwriter's Laboratories to U.S. and Canadian Standards.

Warranty: Limited 5 year warranty (within the Continental Limits of the United States and Canada). Five years on the sealed refrigeration system, one year on most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.



OASIS USA

800.646.2747

info@oasiscoolers.com

oasiscoolers.com

oasis-parts.com

OASIS Europe

Ireland: tel. + 353 96 71222

Poland: tel + 48 32 332 6501

info@oasis.ie

oasis.ie

Specifications are subject to change without notice.

OASIS is a registered trademark of LVD Acquisition, LLC dba Oasis International © 2012