SUMMIT

ASDS2413CSS



32" x 23.38" x 17.75" (H x W x D)

Shallow depth built-in undercounter ADA compliant allrefrigerator with stainless steel exterior and interior, lock, and digital controls

Highlights:

Uniquely shallow depth under 18" for an easy fit in kitchen islands

32" height fits under lower ADA compliant counters

Stainless steel interior cabinet for lasting durability and easier cleanup

Product Features:

24" wide all-refrigerator	3.1 cu.ft. interior for residential or commercial cold storage	
Less than 18" deep	Unique 17.75" shallow depth is ideal for wet bars, island kitchens, and other undercounter areas with limited footprint space	
ADA compliant design	32" height allows easy installation under lower ADA compliant counters	
Adjustable height	Leveling legs can be extended up to 2", with a slide-out kickplate that allows you to raise the overall height from 32" up to 34" if used under more standard sized cabinets	
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter	
Stainless steel interior	Walls and floor are constructed from stainless steel for added strength and easy cleanup	
Stainless steel exterior	Complete stainless steel exterior for true luxury under the counter	
Factory installed lock	Keyed lock for a secure interior (2 keys included)	
Professional handle	Includes a full-length pro handle in chrome	





ASDS2413CSS Specifications:

Height of Cabinet 32.0" (81 cm) Width 23.38" (59 cm) Depth 17.75" (45 cm) Depth with Handle 19.75" (50 cm) Depth with door at 90° 40.0" (102 cm) Capacity 3.1 cu.ft. (88 L) Defrost Type Frost-Free Door Stainless Steel US Electrical Safety ETL Canadian Electrical Safety ETL-C Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz Weight 79.0 lbs. (36 kg)			
Depth 17.75" (45 cm) Depth with Handle 19.75" (50 cm) Depth with door at 90° 40.0" (102 cm) Capacity 3.1 cu.ft. (88 L) Defrost Type Frost-Free Door Stainless Steel Cabinet Stainless Steel US Electrical Safety ETL Canadian Electrical Safety ETL-C Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Depth with Handle 19.75" (50 cm) Depth with door at 90° 40.0" (102 cm) Capacity 3.1 cu.ft. (88 L) Defrost Type Frost-Free Door Stainless Steel Cabinet Stainless Steel US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Depth with door at 90° 40.0" (102 cm) Capacity 3.1 cu.ft. (88 L) Defrost Type Frost-Free Door Stainless Steel Cabinet Stainless Steel US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Capacity 3.1 cu.ft. (88 L) Defrost Type Frost-Free Door Stainless Steel Cabinet Stainless Steel US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Defrost Type Frost-Free Door Stainless Steel Cabinet Stainless Steel US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Door Stainless Steel Cabinet Stainless Steel US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Cabinet Stainless Steel US Electrical Safety ETL Canadian Electrical ETL-C Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
US Electrical Safety ETL Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Canadian Electrical Safety Sanitation ETL-S Energy Usage/Year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Safety Sanitation ETL-S Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Energy Usage/Year 215.0kWh/year Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Amps 1.0 Voltage/Frequency 115 V AC/60 Hz			
Voltage/Frequency 115 V AC/60 Hz			
Weight 79.0 lbs (36 kg)			
70.0 lb3. (50 kg)			
Shipping Weight 100.0 lbs. (45 kg)			
Parts & Labor Warranty 1 Year			
Compressor Warranty 5 Years			
UPC 761101088907			
Refrigerator Features			
Sabbath Mode Yes			
Door Swing RHD			
Reversible Yes			
Height Adjustable Yes			
Shelf Type Chrome			
Shelf Qty 3			
Adjustable Shelves Yes			
Thermostat Type Digital			
Fan Type Interior and Exterior			
Refrigerant Type R600a			
Refrigerant Amount 1.38oz.			
High Side PSI 270.0			
Low Side PSI 105.0			
Level Legs Qty 4			
Interior Light Yes			
Temperature Range 36 to 43°F			

Sound Level	33.1 dB	
Dimensions		
Interior Height	24.25" (62 cm)	
Interior Width	19.5" (50 cm)	
Interior Depth	12.25" (31 cm)	
Compressor Step Height	3.75" (10 cm)	
Compressor Step Width	19.5" (50 cm)	
Compressor Step Depth	4.25" (11 cm)	



