SUMMIT

SPR488BOSCSSPNR



34" x 19" x 17.75" (H x W x D)

Commercially approved indoor/outdoor beverage cooler for built-in or freestanding use with a shallow 17.75" depth, panel-ready door trim, glass door, black interior, and stainless steel wrapped cabinet

Highlights:

Shallow depth under 18" makes it ideal for smaller commercial and residential settings

Designed and constructed for safe use in the outdoors

Panel-ready door frame allows you to create a truly custom look under the counter

Product Features:

Shallow depth	Unique 17 3/4" depth is ideal for home wet bars, island kitchens, and other applications with limited footprint space	
Built-in capable	Make the best use of space by installing your refrigerator under the counter	
Panel-ready door trim	Door frame can be customized with a custom overlay panel (panel frame dimensions: 31 9/16" H x 18 3/4" W at 3/4" minimum thickness)	
Weatherproof design	Approved for use in the outdoors, with a sealed exterior and double pane tempered glass door	
Commercially approved	ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings	
Stainless steel wrapped exterior	Cabinet features 304 grade stainless steel construction for added durability and a professional look	
Double pane tempered glass door	Heat resistant design provides clear view of stored products	
Automatic defrost	Reduced user maintenance with auto defrost system	
Adjustable shelves	Three glass shelves with six positions for optimal storage and easy cleaning	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

info@summitappliance.com


 \checkmark




SPR488BOSCSSPNR Specifications:

Height of Cabinet34.0" (86 cm)Width19.0" (48 cm)Depth17.75" (45 cm)Depth with door at 90°34.75" (88 cm)90°3.13 cu.ft. (89 L)Capacity3.13 cu.ft. (89 L)Defrost TypeAutomaticDoorGlass/Panel-Ready FrameCabinetStainless SteelUS Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)Shipping Weight118.0 lbs. (54 kg)		
Depth17.75" (45 cm)Depth with door at 90°34.75" (88 cm)90°3.13 cu.ft. (89 L)Capacity3.13 cu.ft. (89 L)Defrost TypeAutomaticDoorGlass/Panel-Ready FrameCabinetStainless SteelUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
Depth with door at 90°34.75" (88 cm) 34.75" (88 cm)90°3.13 cu.ft. (89 L)Capacity3.13 cu.ft. (89 L)Defrost TypeAutomaticDoorGlass/Panel-Ready FrameCabinetStainless SteelUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
90°Capacity3.13 cu.ft. (89 L)Defrost TypeAutomaticDoorGlass/Panel-Ready FrameCabinetStainless SteelUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
Defrost TypeAutomaticDoorGlass/Panel-Ready FrameCabinetStainless SteelUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
DoorGlass/Panel-Ready FrameCabinetStainless SteelUS Electrical SafetyETLCanadian Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
FrameCabinetStainless SteelUS Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
US Electrical SafetyETLCanadian ElectricalETL-CSafetySanitationSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
Canadian Electrical SafetyETL-CSanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
SafetySanitationETL-SEnergy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
Energy Usage/Year285.0kWh/yearAmps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
Amps1.3Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
Voltage/Frequency115 V AC/60 HzWeight85.0 lbs. (39 kg)		
Weight 85.0 lbs. (39 kg)		
Shipping Weight 118.0 lbs. (54 kg)		
Parts & Labor 1 Year Warranty		
Compressor Warranty 5 Years		
UPC 761101077819		
Refrigerator Features		
Door Swing RHD		
Reversible Factory Reversible		
Height Adjustable Yes		
Shelf Type Glass		
Shelf Qty 3		
Adjustable Shelves Yes		
Can Storage Yes		
Thermostat Type Dial		
Fan Type Interior		
Refrigerant Type R600a		
Refrigerant Amount 0.88oz.		
High Side PSI 320.0		
Low Side PSI 120.0		
Level Legs Qty 2		
Interior Light Yes		

Temperature Range	34 to 50°F		
Sound Level	32.6 dB		
Dimensions			
Interior Height	29.0" (74 cm)		
Interior Width	16.0" (41 cm)		
Interior Depth	12.75" (32 cm)		
Compressor Step Height	7.0" (18 cm)		
Compressor Step Width	16.0" (41 cm)		
Compressor Step Depth	6.25" (16 cm)		





SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799

