### SUMMIT

# SPR488BOSH34CSS



#### 34" x 19" x 17" (H x W x D)

Commercially approved indoor/outdoor beverage cooler for built-in or freestanding use with a shallow 17.75" depth, seamless stainless steel trimmed glass door, black interior, and stainless steel wrapped cabinet

#### **Highlights:**

Shallow depth under 18" makes it ideal for smaller commercial and residential settings

Designed and constructed for safe use in the outdoors

Commercially listed to NSF-7 standards and meets UL-471 for commercial applications

#### **Product Features:**

Shallow depth	Unique 17 3/4" depth is ideal for home wet bars, island kitchens, and other applications with limited footprint space	
Built-in capable	Make the best use of space by installing your refrigerator under the counter	
Weatherproof design	Approved for use in the outdoors, with a sealed exterior and double pane tempered glass door	
Commercially approved	ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings	
Stainless steel wrapped exterior	Cabinet features 304 grade stainless steel construction for added durability and a professional look	
Double pane tempered glass door	Heat resistant design provides clear view of stored products, with an elegant trim in seamless stainless steel	
Automatic defrost	Reduced user maintenance with auto defrost system	
Adjustable shelves	Three glass shelves with six positions for optimal storage and easy cleaning	
LED lighting	Automatically illuminates when the door is open for an attractive and energy efficient view	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799



## SUMMIT

### SPR488BOSH34CSS Specifications:

Overview		
Height of Cabinet	34.0" (86 cm)	
Width	19.0" (48 cm)	
Depth	17.0" (43 cm)	
Depth with Handle	18.63" (47 cm)	
Depth with door at 90°	34.75" (88 cm)	
Capacity	3.13 cu.ft. (89 L)	
Defrost Type	Automatic	
Door	Glass	
Cabinet	Stainless Steel	
US Electrical Safety	ETL	
Canadian Electrical Safety	ETL-C	
Sanitation	ETL-S	
Energy Usage/Year	285.0kWh/year	
Amps	1.3	
Voltage/Frequency	115 V AC/60 Hz	
Weight	85.0 lbs. (39 kg)	
Shipping Weight	95.0 lbs. (43 kg)	
Parts & Labor Warranty	1 Year	
Compressor Warranty	5 Years	
UPC	761101079325	
Refrigerator Features		
Door Swing	RHD	
Reversible	Yes	
Height Adjustable	Yes	
Shelf Type	Glass	
Shelf Qty	3	
Adjustable Shelves	Yes	
Can Storage	Yes	
Thermostat Type	Dial	
Fan Type	Interior	
Refrigerant Type	R600a	
Refrigerant Amount	0.88oz.	
High Side PSI	320.0	
Low Side PSI	120.0	
Level Legs Qty	2	
Interior Light	Yes	
Temperature Range	34 to 50°F	
Sound Level	32.6 dB	

Dimensions	
Interior Height	29.0" (74 cm)
Interior Width	16.0" (41 cm)
Interior Depth	12.75" (32 cm)
Compressor Step Height	7.0" (18 cm)
Compressor Step Width	16.0" (41 cm)
Compressor Step Depth	6.25" (16 cm)





