SUMMIT

SPR489OSPNR



34" x 19" x 17.75" (H x W x D)

Commercially approved indoor/outdoor beverage cooler for built-in or freestanding use with a shallow 17.75" depth, panel-ready door trim, glass door, and black cabinet

Highlights:

Shallow depth under 18" makes it ideal for smaller commercial and residential settings

Designed and constructed for safe use in the outdoors

Panel-ready door frame allows you to create a truly custom look under the counter

Product Features:

| Shallow depth | Unique 17 3/4" depth is ideal for home wet bars, island kitchens, and other applications with limited footprint space | |
|---------------------------------|--|--|
| Built-in capable | Make the best use of space by installing your refrigerator under the counter | |
| Panel-ready door trim | Door frame can be customized with a custom overlay panel (panel frame dimensions: 31 9/16" H \times 18 3/4" W at 3/4" minimum thickness) | |
| Weatherproof design | Approved for use in the outdoors, with a sealed exterior and double pane tempered glass door | |
| Commercially approved | ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings | |
| Double pane tempered glass door | Heat resistant design provides clear view of stored products | |
| Automatic defrost | Reduced user maintenance with auto defrost system | |
| Adjustable shelves | Three glass shelves with six positions for optimal storage and easy cleaning | |
| LED lighting | Automatically illuminates when the door is open for an attractive and energy efficient view | |







SPR489OSPNR Specifications:

| Overview | | | |
|-------------------------------|----------------------------|--|--|
| Height of Cabinet | 34.0" (86 cm) | | |
| Width | 19.0" (48 cm) | | |
| Depth | 17.75" (45 cm) | | |
| Depth with door at 90° | 34.75" (88 cm) | | |
| Capacity | 3.13 cu.ft. (89 L) | | |
| Defrost Type | Automatic | | |
| Door | Glass/Panel-Ready Frame | | |
| Cabinet | Black | | |
| US Electrical Safety | ETL | | |
| Canadian Electrical Safety | ETL-C | | |
| Sanitation | ETL-S | | |
| Energy Usage/Year | 285.0kWh/year | | |
| Amps | 1.3 | | |
| Voltage/Frequency | 115 V AC/60 Hz | | |
| Weight | 75.0 lbs. (34 kg) | | |
| Shipping Weight | 100.0 lbs. (45 kg) | | |
| Parts & Labor Warranty | 1 Year | | |
| Compressor Warranty | 5 Years | | |
| UPC | 761101074948 | | |
| Refrigerator Features | | | |
| Door Swing | RHD | | |
| Reversible | Factory Reversible | | |
| Height Adjustable | Yes | | |
| Shelf Type | Glass | | |
| Shelf Qty | 3 | | |
| Adjustable Shelves | Yes | | |
| Can Storage | Yes | | |
| Thermostat Type | Dial | | |
| Fan Type | Interior | | |
| Refrigerant Type | R600a | | |
| Refrigerant Amount | 0.88oz. | | |
| High Side PSI | 320.0 | | |
| Low Side PSI | 120.0 | | |
| Level Legs Qty | 2 | | |
| Interior Light | Yes | | |
| | | | |

| Temperature Range | 34 to 50°F |
|---------------------------|----------------|
| Sound Level | 32.6 dB |
| Dimensions | |
| Interior Height | 29.0" (74 cm) |
| Interior Width | 16.0" (41 cm) |
| Interior Depth | 12.75" (32 cm) |
| Compressor Step Height | 7.0" (18 cm) |
| Compressor Step Width | 16.0" (41 cm) |
| Compressor Step Depth | 6.25" (16 cm) |





