QUICK REFERENCE GUIDE



CO29F • 21" ADA Combo® Model • ADA Series

FEATURES & BENEFITS



MODEL DETAILS

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-CO29FB-00A	115 / 60	Field Reversible	Black Solid	101 lbs
U-CO29FW-00A	115 / 60	Field Reversible	White Solid	101 lbs

ACCESSORIES


Model	Description	Finish	Shipping Weight
WATERHOOKUP	Braided water supply line kit	na	2 lbs




ADA Series • 21" ADA Combo® Model • CO29F

DIMENSIONS

Dimensions shown apply to all finishes, including Integrated (INT) models with $\frac{3}{4}$ " integrated panel/frame installed.



CABINET CUT-OUT



INSTALLATION NOTES

Cutout includes the additional $\ensuremath{^{1\!/\!4''}}$ width overall to ensure proper installation.

When installing a left-hand hinge model, allow for 145° door swing for proper removal of ice bin.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

SPECIFICATIONS

Model	CO29F	
Amps: Running	2.5	
Capacity: Bottle (12 oz)	24	
Capacity: Can (12 oz)	44	
Capacity: Refrigerator Volume (cu ft)	2.1	
Control Type	Mechanical Dial	
Defrost Type	Frost Free	
Dimensions: Product Depth	23" / 584 mm	
Dimensions: Product Height	28 ½" / 724 mm	
Dimensions: Product Width	20 7⁄8" / 530 mm	
Energy Consumption: Avg. Per Year	567 kWh	
ENERGY STAR	No	
Ice Production Per Day	8 lbs	
Ice Storage	8 lbs	
Product Weight: Max	92 lbs	
Refrigerant Type	R134A	
Sabbath (Star K Certified)	No	
Temperature Range	34°F - 45°F	

ELECTRICAL REQUIREMENTS

This unit requires a grounded a polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).



Please visit u-line.com to view this model's User Guide. All specifications are subject to change without notice.