



PERLICK®

R
RESIDENTIAL



G5 LUXE 24" DUAL ZONE BEVERAGE CENTER

Crafted with over a century of premier commercial refrigeration expertise, the Perlick G5 collection brings the most innovative refrigeration available into the home—empowering hosts to serve effortlessly, whether for one guest or many.



G5BZ24GL



G5BZ24SL

Job:
Area:
Item #:
Model #:



MODEL NUMBER	ITEM NUMBER	DESCRIPTION
G5BZ24SL	URS24C21-5-SREO	24" DUAL ZONE BEVERAGE CENTER, SOLID DOOR, HINGE RIGHT
G5BZ24GL	URS24C41-5-SREO	24" DUAL ZONE BEVERAGE CENTER, GLASS DOOR, HINGE RIGHT

G5 Luxe Collection Feature-Benefits

- High-Performance Cooling:** Perlick's fastest cool-down speed yet, powered by Perlick's exclusive RAPIDcool™ technology chills every beverage quickly and evenly throughout the cabinet
- Seamless, Beautiful Design:** Sleek cabinet profile and fully concealed, soft-closing hinges integrate effortlessly into surrounding cabinetry
- Commercial-Grade:** Industry-exclusive 300-series stainless steel interiors and exteriors provide corrosion-resistance and durability
- Trusted Performance:** Certified for indoor and outdoor use, delivering consistent performance in kitchens, patios, or rooftop terraces
- Smart Technology:** Adapts to your usage and environment for frost-free, consistent cooling, while continuously monitoring unit health for easy troubleshooting and fast remote support
- Industry's Best Warranty:** 6 years parts and labor, plus a 30-day initial aesthetics parts and labor warranty
- Quick-Cool Mode:** Chills beverages up to 20% faster for on-demand cooling
- Intuitive Touchscreen Controls:** Sleek, modern interface with temperature, lighting, and diagnostics on an easy-to-use interface
- Total Color Control™ LED Lighting:** 20 curated settings, including four distinct white tones, to create any desired aesthetic
- Signature Legacy Handle:** Premium knurled stainless grip with cast end caps embossed with the Perlick emblem
- Ultra-Quiet Performance:** Powered by Perlick-exclusive variable speed technology, delivering quiet operation without compromising cooling power
- Triple-Pane Glass Doors:** Low-E, argon-filled, UV-resistant glass reduces energy transfer and strengthens durability
- Perlick Anti-Condensation System™:** Prevents condensation from forming on the exterior of the cabinet
- Easy Installation:** Patent-pending front-access leveling legs allow quick adjustments without tipping the unit
- Better For The Environment Refrigerant:** This product uses R600a refrigerant which has zero ODP and very low GWP
- Exclusively Perlick:** Exclusively designed, engineered and manufactured by Perlick
- Sabbath Mode-Star K:** Certified that allows equipment to operate in accordance with Halacha, Shabbat, and Jewish Holidays

G5 Luxe Dual Zone Wine And Beverage Center Feature-Benefits

- Preserve the character of fine wines while keeping other beverages perfectly chilled, with two independently controlled zones designed to elevate every entertaining experience
- Store wine bottles horizontally on top half of unit with full-extension, all stainless shelving storage below, perfect for bottles and cans of all sizes
- Upper Zone – Wine: 40°F (4.4°C) – 68°F (20°C), Factory Set Point 55°F (12.8°C)
- Lower Zone – Refrigerator: 33°F (0.6°C) – 42°F (5.6°C), Factory Set Point 38°F (3.3°C)



800.558.5592

perlick.com



PERLICK®



G5 LUXE 24" DUAL ZONE BEVERAGE CENTER

MODEL NUMBERS		G5BZ24SL, G5BZ24GL
MODEL DESCRIPTION		DUAL ZONE BEVERAGE CENTER
OVERALL DIMENSIONS	Width - in. (mm)	23 7/8" (606)
	Depth - in. (mm)	22 1/2" (572)
	Height - in. (mm)	34 5/16" (872)
OPENING DIMENSIONS	Width - in. (mm)	24" (610)
	Depth - in. (mm)	24" (610)
	Height - in. (mm)	34 1/2" (876)
INTERNAL VOLUME Net. Cu. Ft. (L).		4.7 (133)
SHIPPING WEIGHT Lbs. (kg.).		220 (100)
EQUIPMENT WEIGHT Lbs. (kg.).		182 (82)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115VAC/60 Hz/1 Ph
	Running Load Amps	1.9
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
	Lighting Type	LED
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (45g)
	Expansion Device	Capillary Tube
	Temperature Settings F (C)	Upper Zone - Wine: 40°F (4.4°C) - 68°F (20°C) Factory Set Point 55°F (12.8°C)
		Lower Zone - Refrigerator: 33°F (0.6°C) - 42°F (5.6°C) Factory Set Point 38°F (3.3°C)
	Heat Rejection (at 75°F)	450 BTU/hr
	Front Vented	Yes

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com



800.558.5592

perlick.com



PERLICK®

R
RESIDENTIAL

G5 LUXE 24" DUAL ZONE BEVERAGE CENTER

