



PERLICK®

R
RESIDENTIAL



G5 24" REFRIGERATOR

Crafted with over a century of premier commercial refrigeration expertise, the Perlick G5 collection brings the most innovative refrigeration available into the home—empowering hosts to serve effortlessly, whether for one guest or many.



G5RE24GC



G5RE24SC



MODEL NUMBER	ITEM NUMBER	DESCRIPTION
G5RE24SC	URC24R21-5-SRRO	24" REFRIGERATOR, SOLID DOOR, HINGE RIGHT
G5RE24GC	URC24R41-5-SRRO	24" REFRIGERATOR, GLASS DOOR, HINGE RIGHT

G5 Collection Feature-Benefits

- High-Performance Cooling:** Perlick's fastest cool-down speed yet, powered by Perlick's exclusive RAPIDcool™ technology chills every beverage quickly and evenly throughout the cabinet
- Seamless, Beautiful Design:** Sleek cabinet profile and fully concealed, soft-closing hinges integrate effortlessly into surrounding cabinetry
- Trusted Performance:** Certified for indoor and outdoor use, delivering consistent performance in kitchens, patios, or rooftop terraces
- Smart Technology:** Adapts to your usage and environment for frost-free, consistent cooling, while continuously monitoring unit health for easy troubleshooting and fast remote support
- 3-year parts and labor warranty,** 6-year sealed system parts and labor, with 30-day initial aesthetics parts and labor warranty
- Quick-Cool Mode:** Chills beverages up to 20% faster for on-demand cooling
- Intuitive Touchscreen Controls:** Sleek, modern interface with temperature, lighting, and diagnostics on an easy-to-use interface
- Total Color Control™ LED Lighting:** 20 curated settings, including four distinct white tones, to create any desired aesthetic
- Ultra-Quiet Performance:** Powered by Perlick-exclusive variable speed technology, delivering quiet operation without compromising cooling power
- Triple-Pane Glass Doors:** Low-E, argon-filled, UV-resistant glass reduces energy transfer and strengthens durability
- Perlick Anti-Condensation System™:** Prevents condensation from forming on the exterior of the cabinet
- Easy Installation:** Patent-pending front-access leveling legs allow quick adjustments without tipping the unit
- Better For The Environment Refrigerant:** This product uses R600a refrigerant which has zero ODP and very low GWP
- Exclusively Perlick:** Exclusively designed, engineered and manufactured by Perlick
- All stainless-steel interiors and exteriors, with 400-series stainless steel
- Sabbath Mode-Star K certified that allows equipment to operate in accordance with Halacha, Shabbat, and Jewish Holidays

G5 Refrigerator Feature-Benefits

- Designed to hold beverages of any kind making it the perfect companion for every host
- 33°F (0.6°C) – 48°F (8.9°C), Factory Set Point 38°F (3.3°C)



800.558.5592

perlick.com



PERLICK®

R
RESIDENTIAL



G5 24" REFRIGERATOR

MODEL NUMBERS		G5RE24SC, G5RE24GC
MODEL DESCRIPTION		REFRIGERATOR
OVERALL DIMENSIONS	Width - in. (mm)	23 7/8" (606)
	Depth - in. (mm)	22 1/2" (572)
	Height - in. (mm)	34 5/16" (872)
OPENING DIMENSIONS	Width - in. (mm)	24" (610)
	Depth - in. (mm)	24" (610)
	Height - in. (mm)	34 1/2" (876)
INTERNAL VOLUME Net. Cu. Ft. (L).		5.0 (141)
SHIPPING WEIGHT Lbs. (kg.).		194 (88)
EQUIPMENT WEIGHT Lbs. (kg.).		155 (70)
ELECTRICAL SPECIFICATIONS	Electrical Supply	115VAC/60 Hz/1 Ph
	Running Load Amps	1.9
	Electrical Connection	Cord connected
	Cord Plug Type	NEMA 3 Prong 5-15P
	Cord Length	6'
	Defrost Initiation	Automatic
	Defrost Type	Off cycle
	Thermostat	Digital
	Lighting Type	LED
REFRIGERATION SPECIFICATIONS	Refrigerant	R600a (57g)
	Expansion Device	Capillary Tube
	Temperature Settings F (C)	33°F (0.6°C) – 48°F (8.9°C) Factory Set Point 38°F (3.3°C)
	Heat Rejection (at 75°F)	450 BTU/hr
	Front Vented	Yes

Perlick accessories are available for purchase through an authorized Perlick dealer. For a full list of accessories and to find a dealer near you, visit perlick.com


Milwaukee

800.558.5592


perlick.com



PERLICK®





G5 24" REFRIGERATOR



* - Leg levelers can add 3/4" [19] to these dimensions when fully extended.

** - Overlay will add additional 3/4" [19] to overall depth. In addition, overall depth will change depending on handle selected.

*** - Minimum clearance for door swing is shown without door overlay installed




Milwaukee

800.558.5592

perlick.com