

HR24A

Compact Undercounter Reach-in Refrigerator









- Stainless steel exterior
- UL approval for outdoor use
- Energy efficient, one piece ABS interior liner
- Door is stainless steel exterior, aluminum interior and is field reversible
- · Magnetic door gasket is easily removable for cleaning
- Environmentally friendly cyclopentane insulation
- Electronic controls with LED Temperature Display
- High and low temperature alarms as well as "Door Open" alarm
- Ducted air flow for even air distribution throughout the cabinet
- · Cylinder door lock with keys
- Automatic defrost
- (3) Epoxy coated shelves standard
- · Built-in cabinet installation with louvered trim
- * HR24A is ENERGY STAR qualified

Dimensions / Capacity

| Model # | One Section HR24A |
|--|------------------------------------|
| Interior Storage Capacity (CF) (AHAM) | 4.0 ft ³ |
| Amperage | 2.0 |
| Energy Consumption (kwh/day) ENERGY STAR | 0.378 |
| Overall Width x Depth | 23.4" x 24.5" |
| Height | 32.7" |
| Adjustable Shelves | 3 |
| Shelf Dimensions (W x D) | (1) 19.13" x 11", (2) 19.13" x 16" |
| Crated Shipping Weight | 102 lbs |



HR24A 9/11 Item # 13278

Hoshizaki America, Inc. reserves the right to change specifications without notice.

Item #

Project:

Qty:

*AutoCad available on KCL

HR24A Dimensions W x D x H

I Section - 23.4" \times 24.5" \times 32.7"* *with legs

Electrical/Refrigeration

Voltage - 115/60/1

HACR Breaker - 15.0

Electrical Connection - 5-15P (NEMA)

Voltage Range 104 - 127

Ambient Temp. Range 60°- 95°F

Control Setpoint Range 36°-50°F

*Refrigerant R-134A

Warranty

Valid in United States, Canada, Puerto Rico, and U.S. Territories. Contact factory for warranty in other countries.

• Two Year - Parts & Labor on entire machine.

Options

- Epoxy shelves
- · Glass shelves



© HOSHIZAKI AMERICA, INC.


618 Hwy. 74 S., Peachtree City, GA 30269 TEL 800-438-6087 FAX 800-345-1325 www.hoshizaki.com




HR24A Compact Undercounter Reach-in Refrigerator








*For Built-In Applications: Allow 1.2" (30mm) at top for stainless steel louvered vent.











© HOSHIZAKI AMERICA, INC.