









White Solid









Stainless Solid (Flush to Cabinet)

Stainless Solid (Flush to Door)

Stainless Solid (No Flange)

## **Key Features**

Crescent Cube:

- Makes crescent shaped cubes approx.  $^{1}/_{2}"$  W x  $^{3}/_{4}"$  H x 2  $^{1}/_{4}"$  L
- Produces up to 23 lb of ice per day
- Stores 12 lb of ice
- On / off switch
- · White interior

- Stainless steel handle (7/8" diameter)
- Field reversible door is shipped right-hand hinged
- Built-in or freestanding
- No drain required
- 230V model available. See u-line.com for details.


### **Model Details**


Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UMCR014-SC01A	115 / 60	Field Reversible (Flush to Cabinet)	Stainless Solid	66 lb (30 kg)
UMCR014-SD01A	115 / 60	Field Reversible (Flush to Door)	Stainless Solid	66 lb (30 kg)
UMCR014-SS01A	115 / 60	Field Reversible (No Flange)	Stainless Solid	66 lb (30 kg)
UMCR014-BC01A	115 / 60	Field Reversible (Flush to Cabinet)	Black Solid	66 lb (30 kg)
UMCR014-WC01A	115 / 60	Field Reversible (Flush to Cabinet)	White Solid	66 lb (30 kg)


### **Accessories**

Model	Description	Finish	Shipping Weight
ULAWATERHOOKUP	Braided water supply line kit	N/A	2 lb

Front Side Top








# **Specifications**

Specifications		
Model	MCR014	
Amps: Running	2.5 amps	
Amps: Max Start Up	18 amps	
Control Type	On/Off Switch	
Defrost Type	Manual	
Dimensions (NF): Product Depth	17" (432 mm)	
Dimensions (NF): Product Height	25 ½16" (637 mm)	
Dimensions (NF): Product Width	14" (356 mm)	
Dimensions (FC): Product Depth	17" (432 mm)	
Dimensions (FC): Product Height	25 ½" (638 mm)	
Dimensions (FC): Product Width	15 ½" (384 mm)	
Dimensions (FD): Product Depth	17" (432 mm)	
Dimensions (FD): Product Height	26 <sup>1</sup> / <sub>16</sub> " (662 mm)	
Dimensions (FD): Product Width	15 <sup>15</sup> / <sub>16</sub> " (405 mm)	
ENERGY STAR	N/A	
Ice Production Per Day	23 lb (10,4 kg)	
Ice Storage	12 lb (5,4 kg)	
Product Weight: Max	60 lb (25 kg)	
Refrigerant Type	R600a (0.92 oz)	

### Back



### **Cabinet Cut-Out**

Filler Panel (Not Provided by U-Line) – May Be Added Above or Below Unit to Enclose for a Built-In Look See Electrical Specifications for Power Supply Typical Counter Height 34-1/4" Preferred location for electrical outlet 18-1/2" (870 mm) to 35-1/8" (470 mm) is in adjacent cabinet. (892 mm) Cut-Out **®** Height 25-1/16" (637 mm) - 14-3/16"-(360 mm)

### Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)
- + Additional 1 Year (parts & labor) warranty at no cost with product registration

See complete warranty for details



### **Installation Notes**

- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow



